

Package: ggnuplot (via r-universe)

September 14, 2024

Title Make 'ggplot2' Look Like 'gnuplot'

Version 0.1.0

Description Provides a theme, a discrete color palette, and continuous scales to make 'ggplot2' look like 'gnuplot'. This may be helpful if you use both 'ggplot2' and 'gnuplot' in one project.

Imports ggplot2

License MIT + file LICENSE

URL <https://github.com/hriegl/ggnuplot>

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.0

Repository <https://hriegl.r-universe.dev>

RemoteUrl <https://github.com/hriegl/ggnuplot>

RemoteRef HEAD

RemoteSha e5705ce0704b6fc64d951cfc4157013d3bdef504

Contents

scale_color_gnuplot	2
scale_x_gnuplot	3
theme_gnuplot	4

Index	6
--------------	----------

scale_color_gnuplot *The gnuplot color palette for discrete data, ported to ggplot2*

Description

These functions provide gnuplot's default color palette. Use `scale_color_gnuplot()` and `scale_fill_gnuplot()` with `ggplot2`, and `gnupalette()` or the vector `gnucolors` otherwise.

Usage

```
scale_color_gnuplot(..., na.value = "gray50", aesthetics = "color")
scale_fill_gnuplot(..., na.value = "gray50", aesthetics = "fill")
gnupalette(n)
```

Arguments

... Arguments passed on to `discrete_scale`

palette A palette function that when called with a single integer argument (the number of levels in the scale) returns the values that they should take (e.g., `scales::hue_pal()`).

breaks One of:

- `NULL` for no breaks
- `waiver()` for the default breaks (the scale limits)
- A character vector of breaks
- A function that takes the limits as input and returns breaks as output

limits A character vector that defines possible values of the scale and their order.

drop Should unused factor levels be omitted from the scale? The default, `TRUE`, uses the levels that appear in the data; `FALSE` uses all the levels in the factor.

na.translate Unlike continuous scales, discrete scales can easily show missing values, and do so by default. If you want to remove missing values from a discrete scale, specify `na.translate = FALSE`.

scale_name The name of the scale that should be used for error messages associated with this scale.

name The name of the scale. Used as the axis or legend title. If `waiver()`, the default, the name of the scale is taken from the first mapping used for that aesthetic. If `NULL`, the legend title will be omitted.

labels One of:

- `NULL` for no labels
- `waiver()` for the default labels computed by the transformation object
- A character vector giving labels (must be same length as breaks)
- A function that takes the breaks as input and returns labels as output

	<p>expand For position scales, a vector of range expansion constants used to add some padding around the data to ensure that they are placed some distance away from the axes. Use the convenience function <code>expansion()</code> to generate the values for the <code>expand</code> argument. The defaults are to expand the scale by 5% on each side for continuous variables, and by 0.6 units on each side for discrete variables.</p> <p>guide A function used to create a guide or its name. See <code>guides()</code> for more information.</p> <p>position For position scales, The position of the axis. <code>left</code> or <code>right</code> for y axes, <code>top</code> or <code>bottom</code> for x axes.</p> <p>super The super class to use for the constructed scale</p>
<code>na.value</code>	Colour to use for missing values
<code>aesthetics</code>	Character string or vector of character strings listing the name(s) of the aesthetic(s) that this scale works with. This can be useful, for example, to apply colour settings to the <code>colour</code> and <code>fill</code> aesthetics at the same time, via <code>aesthetics = c("colour", "fill")</code> .
<code>n</code>	The number of colors to return

Examples

```
library(ggplot2)

ggplot(iris, aes(Sepal.Width, Sepal.Length, color = Species)) +
  geom_point() +
  scale_color_ggplot() +
  scale_x_ggplot() +
  scale_y_ggplot() +
  theme_ggplot()

gnupalette(3)
gncolors[1:3]
```

scale_x_ggplot *ggplot-like (continuous) axes for ggplot2*

Description

These functions set up ggplot-like secondary axes. They also try to choose pretty breaks/ticks for continuous data. Your mileage with the breaks/ticks may vary, so be sure to try different settings.

Usage

```
scale_x_ggplot(breaks = ggbreaks(), sec.axis = gnuaxis(), ...)
scale_y_ggplot(breaks = ggbreaks(), sec.axis = gnuaxis(), ...)
ggbreaks(n = 5, padding = 0.1)
```

Arguments

breaks	One of: <ul style="list-style-type: none"> • NULL for no breaks • waiver() for the default breaks computed by the transformation object • A numeric vector of positions • A function that takes the limits as input and returns breaks as output (e.g., a function returned by scales::extended_breaks())
sec.axis	sec_axis() is used to specify a secondary axis.
...	Other arguments passed on to scale_(x y)_continuous()
n	The number of breaks/ticks to return
padding	The amount of space between the outermost breaks/ticks and the axis limits relative to the axis range. A number between 0 and 0.5.

See Also

The [labeling package](#) for alternative break/tick functions, and [ggplot2::dup_axis\(\)](#), for which [gnuaxis\(\)](#) is an alias

Examples

```
library(ggplot2)

ggplot(iris, aes(Sepal.Width, Sepal.Length, color = Species)) +
  geom_point() +
  scale_color_gnuplot() +
  scale_x_gnuplot() +
  scale_y_gnuplot() +
  theme_gnuplot()
```

 theme_gnuplot

gnuplot theme for ggplot2

Description

This theme makes ggplot2 look like gnuplot. It is based on [ggplot2::theme_linedraw\(\)](#) and has inward ticks.

Usage

```
theme_gnuplot(
  base_size = 11,
  base_family = "",
  base_line_size = base_size/22,
  base_rect_size = base_size/22
)
```

Arguments

base_size base font size
base_family base font family
base_line_size base size for line elements
base_rect_size base size for rect elements

See Also

The [default ggplot2 themes](#) and `ggplot2::theme()`

Examples

```
library(ggplot2)

ggplot(iris, aes(Sepal.Width, Sepal.Length, color = Species)) +
  geom_point() +
  scale_color_gnuplot() +
  scale_x_gnuplot() +
  scale_y_gnuplot() +
  theme_gnuplot()
```

Index

default ggplot2 themes, [5](#)
discrete_scale, [2](#)

expansion(), [3](#)

ggplot2::dup_axis(), [4](#)
ggplot2::theme(), [5](#)
ggplot2::theme_linedraw(), [4](#)
gnuaxis (scale_x_ggplot), [3](#)
gnubreaks (scale_x_ggplot), [3](#)
gnucolors (scale_color_ggplot), [2](#)
gnupalette (scale_color_ggplot), [2](#)
guides(), [3](#)

labeling package, [4](#)

scale_color_ggplot, [2](#)
scale_colour_ggplot
 (scale_color_ggplot), [2](#)
scale_fill_ggplot
 (scale_color_ggplot), [2](#)
scale_x_ggplot, [3](#)
scale_y_ggplot (scale_x_ggplot), [3](#)
scales::extended_breaks(), [4](#)
scales::hue_pal(), [2](#)
sec_axis(), [4](#)

theme_ggplot, [4](#)
transformation object, [4](#)